

VAPORMIST[®] ELECTRIC HUMIDIFIER

- Adaptable
- Reliable
- Easy to maintain
- Comprehensive control with Vapor-logic® option



VERSATILITY FOR FINISHED SPACES



DriSteem[®] offers Space Distribution Units that match the Vapormist cabinet. See Page 13.

The Vapormist humidifier is a compact, cabinet-style unit compatible with all water types (tap, softened, deionized, reverse osmosis) and numerous dispersion options. Installation is a snap — just attach the frame to a supporting structure and connect electrical and water services.

Available matching Space Distribution Units disperse steam with no visible vapor trail, making Vapormist ideal for use in finished spaces.

COMPREHENSIVE CONTROL WITH VAPOR-LOGIC

Vapormist with Vapor-logic sets new standards for control in electric steam humidification:

Interoperability allows communication with building automation systems via Modbus or with optional BACnet or LonTalk protocols.

Safety presets initiate fill and drain cycles and keep the humidifier cool and safe if sensed conditions, though unlikely, could be hazardous.

Web-enabled control allows you to set up, view, and adjust humidifier functions via Ethernet, either directly or remotely through a network.



STATUS ALARN	DIAGNOSTICS	SETUP	HELP
System Status SPACE SET RH POINT OU 3396 3596 12	Nonday, Decemb View all humidifier cannot be changed 3%	settings below. I from this page.	8:40:18 AM Data stream is LIVI Some settings can be changed here. Go to the Setup tab to change settings that
	TANK STATUS:		
UNMODE Auto	Run Mode	Aub	to Execution
and the second second second	Space RH	339	N
TANK Boiling	RH set point	357	S CRANE
STATUS	Input signal	9.3	I må
	Steam output	12.3	3%
llarms	Steam production	37.4	A lbs/hr
0 active alarms	Duct HL switch	Clo	osed
View Alarma	Tank temperature	194	497
	Tank temp signal	163	37 Ohms
lessages	High water probe	Wat	Mer
0 active messages	Mid water probe	Wat	Aer
View Messages	Low water probe	Wat	der
	Fill valve	Clo	bled
	Drain valve	Clo	beed
	Airflow switch	Flow	
	Interlock switch	Clo	used
	H2O until drain/flue	sh. 912	20 lbs
	H20 until service	304	4000 lbs
	High probe signal	1	
	Mid probe signal	1	
	Low probe signal	1	

VAPORMIST FEATURES AND BENEFITS

VERSATILE

- Uses tap, softened, or RO/DI water
- Capacity from 6 to 102 lbs/hr (2.7 to 46 kg/h), link up to 16 units for capacity up to 1632 lbs/hr (740 kg/h)
- Disperses steam through ductwork with dispersion tubes or panels, or directly into a room with a Space Distribution Unit (SDU) mounted remotely or on top of the Vapormist

FLEXIBLE

- Control to ±3% RH
- On-off or time-proportioned (TP) control for application control in most environments; solid-state relay (SSR) option for tight control
- Electronically monitored water level ensures safe and reliable operation

EASY TO MAINTAIN

- Removable cover allows easy access to evaporating chamber and electrical connections
- Softened water significantly reduces maintenance requirements
- End-of-season autodrain minimizes microbial growth
- User-adjustable water skimmer skims off floating minerals
- Controller-operated drain and flush removes precipitated minerals from evaporating chamber
- Constant thermal expansion and contraction of heating elements continuously sheds mineral buildup

DRISTEEM DISPERSION: PROVEN AND GUARANTEED

When it comes to absorption performance, competitors don't come close to DriSteem's proven and guaranteed dispersion systems. Define your dispersion requirements and DriSteem will meet or exceed them. Guaranteed.

SAVE EVEN MORE ENERGY WITH OUR HIGH-EFFICIENCY TUBE OPTION

An option for new and existing Ultra-sorb® and Rapid-sorb® dispersion assemblies, High-Efficiency Tubes provide significant energy savings: Wasted energy is reduced by up to 85%. Airstream heat gain and condensate are also significantly lowered. See Page 12 for more information.





Discover how building owners and developers can leverage humidification as a competitive advantage.

Scan the QR code with your smart phone or visit www.dristeem.com/resources-for-contractors

VAPOR-LOGIC CONTROLLER

KEYPAD/DISPLAY



WEB INTERFACE

ATATAM COMPANYS	TRAVELENCE AN	100 No. 1						
Tartine Mater Marcine States Marcine Marcine Provide	Manday, Socialitar (0), 1913 10(4),19 AN Sen al have for artists tons. Some officer on to darged here, do to the Sone Sol sense for charged from the page.							
3349 3349 12:349	Terre Linkson	11						
ALC: NOTE: ALC: NOTE: NO	Tax Auto	Auto	A COMPANY OF THE OWNER OWNER OF THE OWNER OWNER OWNER OWNER OWNER OWNER OWNER					
	Taxas In.	25%	and the second se					
THEN AND IN CASE	THE red wind	10%	Transmitt 1					
COURSE .	International In	B.F.M.						
and the second s	Start adult	10.0%						
Alatant	Burn and allow	STA Market						
O antibus alignment.	Dart M. outsh	diand						
· stan.line.	Tati tengarature	1000						
	Park Note signal	44.00° (18-ma						
WOMEN'S	real costs proces	NOW!						
Matchie terrages	titel a data prime	'Bulk'						
+ distillanated	Low support strates	Muter.						
	prd cates	Classif.						
	CARR NEWS	Clant						
	Infan article	750						
	Distant and all	Contract of Contra						
	BLE INF BUILD	BUE NO						
	Berryes blac D3re	Jonation State						
	The public served	B						
	Intel probe signal	- 4						
	Law probe pages							



ACCURATE, RESPONSIVE CONTROL

The Vapor-logic controller provides accurate, responsive RH control. PID control tunes the system for maximum performance.

Modbus, BACnet, or LonTalk allow interoperability with multiple building automation systems. Modbus is standard, and BACnet or LonTalk are available options.

Web interface provides the capability to set up, view, and adjust humidifier functions via Ethernet, either directly or remotely through a network.

Cycle counter triggers a message when it's time to replace the contactor.

USB port allows easy firmware updates, and data backup and restore capability.

Real-time clock allows time-stamped alarm and message tracking, and accurate drain and flush scheduling.

Auxiliary temperature sensor/transmitter allows air temperature monitoring, such as in a duct, and enables temperature compensation to prevent window condensation.

Programmable outputs allow remote signaling and device activation.

Multiple-humidifier control allows staged control of up to 16 humidifiers with one controller.

Controller data, such as RH, air temperature, water use, energy use, alarms, and messages, can be downloaded to a PC for viewing and analysis. RH, alarms, and messages can also be viewed on the keypad/display and Web interface.

Enhanced diagnostics include:

- **Test outputs** function using keypad/display or Web interface to verify component operation
- Test humidifier function using simulated demand to validate performance

VAPORMIST PRINCIPLE OF OPERATION

VAPORMIST PRINCIPLE OF OPERATION



- 1. When the system is first activated, the fill valve opens and the evaporating chamber fills with water to the operating level.
- 2. On a call for humidity, the heating elements are energized, causing the water to boil. The fill valve opens and closes as needed to maintain the operating water level.
- 3. During refill in tap/softened water systems, a portion of the surface water is skimmed off, carrying away precipitated minerals.

Systems with the RO/DI water option (using deionized water or water that has been treated using reverse osmosis) do not require skimming.

4. Steam created in the evaporating chamber flows through steam hose, tubing, or piping to the dispersion assembly, where it is discharged into the airstream.

VAPORMIST COMPONENTS

VAPOR-LOGIC KEYPAD/DISPLAY

VAPORMIST COMPONENTS





1. VAPOR-LOGIC CONTROLLER

Vapor-logic controls all humidifier functions and can connect to a building automation system via Modbus or optional BACnet or LonTalk. See Page 4 for more information.

2. WATER LEVEL CONTROL

Tap/softened water systems control water levels electronically using a threerod probe, see figure at right.

Systems with the RO/DI water option control water levels using a float valve, see figure at right, and low-water cutoff switch.

3. DRAIN

Duration and frequency of draining are user adjustable. To avoid possible stagnant water and microbial growth, the humidifier automatically drains if there is no call for humidity after a user-defined time period (72-hour default).

VAPORMIST COMPONENTS

4. WATER SKIMMER/OVERFLOW PORT

In tap/softened water systems, the water skimmer reduces surface minerals in the evaporating chamber. Skimming occurs each time the humidifier fills. The skim time duration is user-adjustable.

Systems with the RO/DI water option do not require skimming; the skimmer port functions as an overflow port.

5. HEATING ELEMENTS

Low-watt-density Incoloy-sheathed heating elements ensure operation for many seasons. Constant expansion and contraction of heating elements sheds mineral scale. In the unlikely event of heater failure, heating elements can be removed easily.

6. REMOVABLE COVER

A removable cover allows easy access to the evaporating chamber, electrical connections, and drain.

7. STEAM OUTLET

Steam generated in the humidifier rises through the steam outlet and travels to the dispersion assembly through vapor hose or piping.

8. TEMPERATURE SENSOR (NOT SHOWN)

Mounted on the evaporating chamber, this sensor enables:

- Over-temperature protection
- Freeze protection
- Preheating, allowing rapid response to a call for humidity

WATER LEVEL CONTROL FOR TAP/ SOFTENED WATER HUMIDIFIER



Humidifiers using tap or softened water control water levels electronically using a three-rod probe. The controller responds with the above actions when the water level reaches each rod.

WATER LEVEL CONTROL FOR RO/DI WATER OPTION HUMIDIFIER



Humidifiers using RO/DI water control water levels using a float valve and low-water cutoff switch.

VAPORMIST SPECIFICATIONS

Table 8-1: Vapormist capacities, electrical specifications, and weights																
VM M model	Maximum steam		Current draw (amps)								Weights ‡					
	cap	capacity		Single-phase					Three-phase			Shipping		Operating		
kW	lbs/hr	kg/hr	120V	208V*	240V*	277V	480V†	600V†	208V*	240V†	480V†	600V†	lbs	kg	lbs	kg
2	6	2.7	16.7	9.6	8.3	7.2	4.2	3.3	_	_	_	_	80	36	95	43
4	12	5.4	33.3	19.2	16.7	14.4	8.3	6.7	16.7**	14.4**	7.2**	5.8**	80	36	95	43
6	18	8.2	_	28.8	25.0	21.7	12.5	10.0	25.0**	21.7**	10.8**	8.7**	88	40	122	55
8	24	10.9	_	38.5	33.3	28.9	16.7	13.3	33.3**	28.9**	14.4**	11.5**	88	40	122	55
10	30	13.6	_	-	41.7	36.1	20.8	16.7	29.1**	25.3**	12.6**	10.1 * *	93	42	139	63
12	36	16.3	_	_	-	43.3	25.0	20.0	33.3	28.9	14.4	11.5	93	42	139	63
14	42	19.1	_	-	_	_	29.2	23.3	38.9	33.7	16.8	13.5	93	42	139	63
16	48	21.8	_	_	-	_	33.3	26.7	44.4	38.5	19.2	15.4	93	42	139	63
21	63	28.6	_	-	-	_	43.8	35.0	_	_	25.3	20.2	95	43	152	69
25	75	34.0	_	_	_	_	_	41.7	_	_	30.1	24.1	95	43	152	69
30	90	40.9	_	_	_	_	_	_	_	_	36.1	28.9	101	46	156	71
34	102	46.3	_	_	_	_	_	_			40.9	32.7	101	46	156	71

* On 208V/240V/single-phase/three-wire and on 208V/three-phase/four-wire supplies, the neutral line provides a separate 120V circuit for the SDU fan unit.

** For wire sizing, the highest leg draw is shown due to current imbalance.

+ Add the following to Vapormist weights if using an SDU option (these weights are for additional control components housed within the Vapormist cabinet):

– SDU-I: 12 lbs (5.5 kg) (SDU-I shipping weight is 68 lbs [31 kg])

– SDU-E: 9 lbs (4 kg) (SDU-E shipping weight is 61 lbs [28 kg])

‡ Add the following if using the SSR option:

- For single-phase or three-phase models drawing less than 32.7 amps, add 2 lbs (1 kg)

- For three-phase models drawing more than 32.7 amps, add 4 lbs (2 kg)

All Vapormist models operate at 50/60 Hz.

하지? 사람은 사람은 것을 다 같은 것이 아파를 들었다. 비용을 다 있는 것이 것

VAPORMIST SPECIFICATIONS

VAPORMIST CLEARANCE RECOMMENDATIONS

Maintain these clearances for service and maintenance.



22

VAPORMIST DIMENSIONS

VAPORMIST DIMENSIONS



VAPORMIST PIPING: TAP/SOFTENED WATER

VAPORMIST (TAP/SOFTENED WATER) FIELD PIPING OVERVIEW



Notes:

- Locate air gap only in spaces with adequate temperature and air movement to absorb flash steam; otherwise, condensation may form on nearby surfaces. Refer to governing codes for drain pipe size and maximum discharge water temperature.
- Offset humidifier from spill funnel or floor drain to prevent flash steam from rising into cabinet.
- Dashed lines indicate provided by installer.
- Water supply inlet is more than 1" (25 mm) above skim/overflow port, eliminating the possibility of backflow or siphoning from tank. No additional backflow prevention is required; however, governing codes prevail.
- Install a union in water supply and drain lines as shown to allow tank removal.
- Damage caused by chloride corrosion is not covered by your DriSteem warranty.

VAPORMIST PIPING: RO/DI WATER OPTION

VAPORMIST (RO/DI WATER) FIELD PIPING OVERVIEW



Notes:

- Locate air gap only in spaces with adequate temperature and air movement to absorb flash steam; otherwise, condensation may form on nearby surfaces. Refer to governing codes for drain pipe size and maximum discharge water temperature.
- Offset humidifier from spill funnel or floor drain to prevent flash steam from rising into the cabinet.
- Dashed lines indicate provided by installer.
- The water supply inlet is more than 1" (25 mm) above the overflow port, eliminating the possibility of backflow or siphoning from the tank. No additional backflow prevention is required; however, governing codes prevail.
- Install a union in the water supply and drain lines as shown to allow tank removal.
- Damage caused by chloride corrosion is not covered by your DriSteem warranty.

VAPORMIST STEAM DISPERSION OPTIONS



Ultra-sorb Models LV



Ultra-sorb Models LH

ULTRA-SORB MODELS LV AND LH

Most versatile

- Guaranteed, short non-wetting distances install within inches of downstream devices
- Reduce wasted energy up to 85% and increase capacity with optional High-Efficiency Dispersion Tubes
- Lowest installation cost factory assembly for easy installation

Capacity: Up to 1850 lbs/hr (840 kg/h) per panel

HIGH-EFFICIENCY DISPERSION TUBES OPTION

For new and existing Ultra-sorb, Rapid-sorb, single dispersion tube

- Highest efficiency
- Increases tube capacity up to 6 lbs/hr (2.7 kg/h)
- Up to 85% reduction in wasted energy, airstream heat gain, and condensate production



• Plenum approved for in-duct installation



Rapid-sorb with High-Efficiency Tubes



Ultra-sorb Model LV with High-Efficiency Tubes

VAPORMIST STEAM DISPERSION OPTIONS

RAPID-SORB® DISPERSION TUBE SYSTEM

Multiple tubes, short non-wetting distance

- Short non-wetting distance, compared to single dispersion tube
- Horizontal or vertical airflows •
- Install Rapid-sorb header inside or outside duct
- Available with High-Efficiency Dispersion Tubes •

Capacity: Up to 2100 lbs/hr (955 kg/h) per system

SINGLE DISPERSION TUBE

Installation flexibility

- Low-capacity dispersion for horizontal or vertical airflows.
- Available as a High-Efficiency Dispersion Tube

Capacity: Up to 97 lbs/hr (38 kg/h)

SPACE DISTRIBUTION UNITS

Quiet, fan-based steam dispersion

- SDUs mount on top of Vapormist humidifiers or remotely
- Designed for finished spaces •

Capacity: Up to 102 lbs/hr (46.3 kg/h)



Rapid-sorb dispersion tube system







SDU mounted on Vapormist humidifier

NOTES

DRI-STEEM Corporation

A subsidiary of Research Products Corporation An ISO 9001:2000 certified company

U.S. Headquarters: 14949 Technology Drive Eden Prairie, MN 55344 800-328-4447 or 952-949-2415 952-229-3200 (fax)

Continuous product improvement is a policy of DriSteem Corporation; therefore, product features and specifications are subject to change without notice.

DriSteem, Rapid-sorb, Ultra-sorb, Vapor-logic, and Vapormist are registered trademarks of DriSteem Corporation and are filed for trademark registration in Canada and the European community.

Product and corporate names used in this document may be trademarks or registered trademarks. They are used for explanation only without intent to infringe.

© 2021 DriSteem Corporation



Form No. VM-CAT-EN-2021-1221

Expect quality from the industry leader

For more than 45 years, DriSteem has been leading the industry with creative and reliable humidification solutions. Our focus on quality is evident in the construction of DriSteem products. DriSteem leads the industry with a Two-year Limited Warranty and optional extended warranty.

For more information www.dristeem.com sales@dristeem.com

For the most recent product information visit our website: www.dristeem.com

